

## Permanent Light 826 / Bulb

## **Bulb 15W BA15D 24V**



Part No.: 955.826.35

| MECHANICAL DATA       |        |
|-----------------------|--------|
| Height                | 48 mm  |
| Diameter              | 22 mm  |
| Housing colour        | Silver |
| Weight with packaging | 10 g   |
| Product weight        | 8 g    |

| ELECTRICAL DATA             |          |  |
|-----------------------------|----------|--|
| Operating voltage           | 24V      |  |
| Operating voltage frequency | 50Hz     |  |
| Operating voltage tolerance | +/- 10%  |  |
| Rated operational voltage   | 24 VDC   |  |
| Rated operational current   | 625 mA   |  |
| Rated inrush current        | 6.250 mA |  |
| Power illuminant            | 15 W     |  |

| OPTICAL DATA        |       |
|---------------------|-------|
| Lamp fitting/socket | BA15d |

| APPROVAL DATA                |                                |  |
|------------------------------|--------------------------------|--|
| Conforms with CE             | No                             |  |
| Conforms with RoHS directive | Fulfills substance restriction |  |
| WEEE                         | No                             |  |
| Conforms with ATEX-directive | No                             |  |
| Conforms with CCC            | No                             |  |
| Conforms with FCC            | No                             |  |
| Conforms with IC             | No                             |  |
| EAC certificate available    | No                             |  |
| Conforms with AS-I           | No                             |  |
| ICAO Certification           | No                             |  |
| Conforms with DNV            | No                             |  |
| Conforms with RoHS CN        | No                             |  |

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.