Maxi free-standing Beacons / EvoSIGNAL Maxi Rotating 115-230VAC CL



ļ

Part No.:	262.440.60	
Series:	EvoSIGNAL	
MECHANI	CAL DATA	
Height		173 mm
Diameter		120 mm
Materials		PC PC/ABS
Dome colour		Clear
Housing colour		Grey
Protection category		IP66
Connection		Push-in terminal
cross-sectional area minimum		0,25mm ² / 24AWG
cross-sectional area maximum		1,50mm² / 16AWG
Type of fixing		Adapter required
Working temperature minimum		n -30°C
Working temperature maximum		n +60°C
Weight with packaging		546 g
Product weight		446 g
ELECTRIC	AL DATA	
Operating voltage		115-230V
Operating voltage type		AC
Operating voltage frequency		50Hz at 230V 60Hz at 115V
Operating voltage tolerance		+/- 10%
Rated operational voltage		230 VAC
Rated operational current		170 mA
Rated inrush current		<6000 mA
Protection class		Protection class 2
Pollution degree		3
Overvoltage category		II
Isolation voltage		Ui = 250V; Uimp = 2.500V
OPTICAL I	DATA	
Light source		LED
Light colour		White
Optical signal image		Revolving
Service life	optical	50,000 h minimum
Rotation speed (rpm)		180 U/min
Pulse- & pa	use Duration [ms]	550N, 2780FF
APPROVA	L DATA	
Conforms with CE		Yes


For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

ļ

Maxi free-standing Beacons / EvoSIGNAL Maxi Rotating 115-230VAC CL

Conforms with RoHS directive	Yes
WEEE	Yes
Conforms with ATEX-directive	No
Conforms with CCC	Yes
Conforms with UL	cULus
UL Type Rating	Type 12
Conforms with FCC	No
Conforms with IC	No
EAC certificate available	Yes
Conforms with UKCA (Importer)	Yes (WERMA (UK) Ltd.)
Conforms with AS-I	No
ICAO Certification	No
Conforms with DNV	No
Conforms with RoHS CN	No
Conforms with VdS	No
MTTF-value [years]	242

DRAWING



For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.