

#### Completely pre-assembled Signal Towers / eSIGN

## eSIGN IO-Link 15 Segments WH



art No.:	657.710.55		c (UL) us
eries:	eSIGN	7	c <b>QL</b> ) us

MECHANICAL DATA		
Height	372 mm	
Diameter	72 mm	
Materials	PC	
Dome colour	Tranclucent	
Housing colour	White	
Protection category	IP66 IP69K	
Connection	M12 plug 4-pole	
Type of fixing	Base mounting Tube mounting	
Working temperature minimum	-30°C	
Working temperature maximum	+60°C	
Weight with packaging	847 g	
Product weight	791 g	
IK-Code (IEC 62262)	IK08	

ELECTRICAL DATA		
Operating voltage	24V	
Operating voltage type	DC	
Operating voltage tolerance	+/- 20%	
Rated operational voltage	24 VDC	
Rated operational current	555 mA	
Rated inrush current	800 mA	
Protection class	Protection class 3	
Pollution degree	3	
Overvoltage category	I	
Isolation voltage	Ui = 50V / Uimp = 330V	
Request to external PSU	SELV/PELV	
connectivity	IO-Link	

OPTICAL DATA		
Light source	LED	
Light colour	MC >1.000.000 colours	
Optical signal image	Blink Double flash Flash Permanent	
Blink frequency	Configurable	
Service life optical	50,000 h maximum	

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.



#### Completely pre-assembled Signal Towers / eSIGN

## eSIGN IO-Link 15 Segments WH

APPROVAL DATA			
Conforms with CE	Yes		
Conforms with RoHS directive	Yes		
WEEE	Yes		
Conforms with ATEX-directive	No		
Conforms with CCC-Ex	No		
Conforms with CCC	No		
Conforms with UL	cULus		
UL Type Rating	Type 4/4X/12/13		
Conforms with FCC	No		
Conforms with IC	No		
EAC certificate available	No		
Conforms with UKCA (Importer)	Yes (WERMA (UK) Ltd.)		
Conforms with CMIM	No		
Conforms with AS-I	No		
Conforms with DNV	No		
Conforms with RoHS CN	No		
Conforms with VdS	No		
MTTF-value [years]	34		

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.



Completely pre-assembled Signal Towers / eSIGN

### eSIGN IO-Link 15 Segments WH

# **DRAWING** Innerer Ring austrennbar für Rohrmontage/ Inner ring can be removed for tube mounting Ø6 Ø72,5 342 Ø54 Ø72,5

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.